

SCOPE OF DELIVERY SF 33

SUPERFINISH 33 PRO	2388260
SuperFinish 33 Pro basic unit	-
Suction system; flexible	34630
HD hose DN6 PN270 1/4" NPSM 15m	9984574
Vector Pro Airless gun; 1/4"; incl. TradeTip 3 nozzle holder; with 4-finger trigger	538040
TradeTip 3 nozzle 523 incl. white filter	553523



INNOVATION SINCE 1947

Perfect surfaces and added value are our passion. Bringing colour, protection and function to surfaces is our mission. We dedicate all of our technical expertise to your objects and products, and support you with personal service. Using innovative technologies and highly efficient, reliable and user-friendly solutions, we are constantly setting new standards in surface technology.



wagner-group.com/3plus2

Anyone purchasing a WAGNER paint spraying unit automatically receives a three-year manufacturer's warranty. But we can do more: If you register online, you can extend this warranty for a further two years, free of charge!

HEA TECHNOLOGY

HEA stands for High Efficiency Airless, the innovative nozzle technology revolutionising airless spraying. HEA tips allow the pressure of the spray device to be reduced and provide exceptional spray results while working in a low pressure range (ideally at 80 - 140 bar). The tips can be used with all TradeTip 3 tip holders and WAGNER devices.



Paint application

wagner-group.com/hea-protip

Standard airless technology



Paint application

THE PUMP FOR EVERY PROJECT

VERSATILITY IN TERMS OF APPLICATIONS AND MATERIALS:

thanks to the vibration-reducing WAGNER QLS technology with a longer diaphragm stroke, an extensive range of materials can be processed across a wide spectrum of application areas and project sizes. Small quantities can be processed with low loss thanks to the easy-to-clean top container.

EFFICIENCY AND PRODUCTIVITY:

with a delivery rate of 4.3 l/min, the SuperFinish 33 is the most powerful WAGNER diaphragm device in the professional segment. It delivers on average a 20% performance increase over its predecessor model, the SuperFinish 31. This ensures that projects can be finished quickly, professionally and economically.

3. LESS OVERSPRAY:

especially for painting work, a low spray pressure offers the advantage of a better spray pattern, less overspray and a more controlled application of paint. Diaphragm pumps permit the variable regulation of pressure from 0 to 250 bar. This means optimal atomisation is possible even at lower pressure settings (30-40 bar). The revolutionary low-pressure Airless WAGNER HEA ProTip nozzle lets you work with up to 55% less overspray.

SIMPLE HANDLING:

the system's extreme ease of use means anyone can quickly get to grips with it – even employees without extensive technical know-how. As an additional bonus, the basic unit of both versions includes an integrated toolbox. This ensures that nozzles, filters and tools are always available.

PRACTICAL MULTI-GUN OPERATION:

do you need even more power? No problem! For parallel use, a distributor adapter for the connection of up to three guns is available separately as an accessory (item No. 2304 430).

QUICK HELP



wagner-group.com/tips-tricks

ACCESSORIES

SUPERFINISH 33 ACCESSORIES

Hopper set, 5 litre; M36x2	0341265
Hopper set, 20 litre; M36x2	0341266
Nozzle extension, 15 cm, G-thread, with holder without nozzle	0556074
Hose reel HR30; M16x1.5	2392523

GUNS / DÜSEN

Vector Grip Airless gun; 1/4"; incl. TradeTip 3 nozzle holder; with 2 and 4-finger trigger	538043
TradeTip 3 nozzles	0553XXX
HEA ProTip nozzles	0554XXX

OTHERS

InlineRoller packaged in a plastic box, incl. HP hose DN4, 27 MPa, 7.5 m, extension complete 0.5 m, woven plush paint roller short pile 13 mm, and so on	0345010
Adapter for multi-gun operation (up to 3 guns)	2304430
Double connector A = 1/4" x 1/4"	34038
Suction system for containers, C-coupling, curved connection, 1.4 m	97082

Subject to changes · EN · 2413798 · 2020



SUPERFINISH 33 PRO

BE UNSTOPPABLE!

wagner-group.com/contractor

SUPERFINISH 33 Pro

Weight	43 kg
Motor output	2,2 kW
Voltage	230 V / 50 Hz
Max. nozzle size	0,033"
Max. operating pressure	250 bar, 25 MPa
Max. delivery rate	4,3 l / min
Max. Viscosity	25.000 mPas
Article number	2388260



More about SuperFinish 33 Pro online:
wagner-group.com/sf33pro

Ergonomic working: with the Vector Pro airless gun. It is lightweight and robust.



Easy transport: robust cart with height-adjustable handle.

Inlet pusher valve: for a high operating reliability and easy commissioning. Just the press of a finger, and the valve is free.

Robust, building-site-friendly tires: allow easy transport across even the most challenging terrain.

Large variety of materials with QLS long-stroke technology: made possible thanks to optimised hydraulics and special valve technology.



CONNECTION OF UP TO THREE GUNS

So you can work 3 times as fast! Accessories are available separately (Art. No. 2304430).

DIAPHRAGM PUMP

Do you want to process different materials, from primers to silicate paints with just one device? Then a WAGNER diaphragm pump is the ideal choice. This powerful, maintenance-friendly technology transports the material via a lifting motion of the diaphragm. Diaphragm pumps from WAGNER are robust, easy-to-use construction site and workshop units.

1. ALSO SUITABLE FOR VERY SMALL VOLUMES:

Diaphragm pumps have up to 58 per cent less material in their system. The device's small cross-sections means that it can also be operated with tiny amounts of material. This saves resources both when changing material and during the cleaning process.

2. LOW-MAINTENANCE AND DURABLE:

The reduced lifting frequency of the diaphragm means that the already lower number of wear parts are placed under significantly less stress. This significantly reduces maintenance costs. Should a repair be necessary, however, the corresponding components can be easily replaced directly on site and in the case of both valves for example, within minutes.

3. FINE AND EVEN SPRAY PATTERN:

Diaphragm technology reduces the pulsation of the material flow, which avoids any irregularities in the spray pattern. It remains fine and even. The piston's switching point is also dispensed with in a diaphragm pump.

*Compared to other piston pumps on the market

 irregular spray pattern from the piston pump


 even spray pattern from the diaphragm pump




More about technology:
wagner-group.com/technologies

RECOMMENDED USE

MATERIALS:


 Water and solvent-based lacquers, lacquer paints, oils, separating agents

 Synthetic resin varnishes, PVC lacquers, 2K lacquers


 Primers, fillers

 Fire protection, rust protection paints

 Emulsion and latex paints, adhesives, sealants

 Exterior paints, roof coatings, floor coatings, textured paint

OBJECT SIZE:



SPRAYGUIDES

This is where you'll find answers about how to set up your device to suit the material and which paints and lacquers give the best spray results with your WAGNER model.
sprayguide.wagner-group.com

