



materials with only one unit.

www.wagner-group.com

## Save time & costs!

The mixing and dosing unit WAGNER 2K COMFORT is also available with two fluid circuits that can be applied in parallel.

- Physical separation of the materials avoids unit downtimes especially with highly reactive materials.
- Up to 50% shorter cycle time of the objects compared to the previous model FlexControl Plus.
- Investment cost savings of up to 15% in comparison to an application with two one-circuit units.

# Selectable alignment of the fluid cabinets

Optimized positioning depending on available space

#### **Individual solutions**

Just as the 2K COMFORT basic version, the two-circuit version can be adapted to specific requirements



### Separate operating elements for each fluid circuit

Start, stop, flushing, recipe change No downtime costs due to operating errors

### Flexible operation

Input of parameters & recipes possible via touch display or mobile device

### **Easy parametrization**

The background color of the display indicates clearly which fluid circuit is parametrized - saves time and avoids errors

Characteristics	2K COMFORT with two fluid circuits
Mixing accuracy	+/-1%
Mixing ratio	0.1:1-50:1
Material pressure	Max. 325 bar
A components	Max. 10 per fluid circuit
B components	Max. 5 per fluid circuit
C components	Max. 5 per fluid circuit



1: ee			(2)
A:B		1.00	:1
Pot life	0	100	min
	<b>①</b>	100	min
A Henu +	Act bond	PC	



J. Wagner GmbH Industrial Solutions D-88677 Markdorf **Tel +49 (0) 7544 505 - 0** Fax +49 (0) 7544 505 - 1200

J. Wagner AG Industrial Solutions CH-9450 Altstätten/SG **Tel +41 (0) 71 7572211** Fax +41 (0) 71 7572323

