

A new perspective!



WAGNER
EvoMotion
40-15
upside-down

Maximum application efficiency.
Ideal for highly viscous materials.
Reduced solvent consumption and waste.

High pressure, highly efficient

The **WAGNER EvoMotion 40-15** high-pressure piston pump in a new shape: Turned upside-down and combined with a 5 L hopper, it ensures maximum application efficiency and material savings - even with viscous material.

- Up to 40% reduction in solvent consumption and material waste during color changes and flushing.
- Ideal for small quantities of paint or frequent color changes.

Suction system

Intake system with 5 L hopper to ensure reduced volume of suction circuit and immediate priming of the pump. The gravitation facilitates working with viscous material.

Operation panel

The spraypack is equipped with a panel front to adjust the main operating parameters with high user-friendliness.

AirCoat gun

AirCoat gun GM 4700AC and material hose package.

Support

Ensures maximum stability of the spraypack.

EvoMotion 40-15

High-pressure piston pump, ideal for both Airless and AirCoat applications. Made of stainless steel and extremely reliable.

Technical data	
Pressure ratio	40:1
Max. air supply pressure	7 bar
Max. material pressure	250 bar
Double stroke volume	15 cm ³ / DS



J. Wagner GmbH
Industrial Solutions
D-88677 Markdorf
Tel +49 (0) 7544 505-0
Fax +49 (0) 7544 505-1200

J. Wagner AG
Industrial Solutions
CH-9450 Altstätten/SG
Tel +41 (0) 71 7572211
Fax +41 (0) 71 7572323



www.wagner-group.com