

WAGNER



PROSPRAY
Piston pumps

BE UNSTOPPABLE!

go.wagner-group.com/contractor

ELECTRIC PISTON PUMP

Especially high suction and delivery performance – across the range

Do you mostly work with viscose or filler materials? Then an electric WAGNER piston pump is the the best support for you. The high suction power produced by the piston's lifting motion makes it ideal for this type of material.

Various performance classes for professional and semi-professional users:

With the third generation of piston pumps from WAGNER, you have a choice of machines for large or small sites. They cover a broad range of paints and emulsions - right through to high-viscosity and filler materials for interior and exterior use.

1. BRUSHLESS MOTOR:

Brushless motors are a real benefit for this device, especially in terms of its long service life. Alongside its efficient mode of working, its key advantages include a constantly high torque with low power consumption and reduced heat generation.


A powerful companion - inside and out:

WAGNER piston pumps are available with three different drive systems. Electric piston pumps cover a wide range of performance classes and have a compact design. The hydraulic piston pumps offer even better performance and are available with a choice of either petrol or electric motors which can be switched in a few minutes. Pneumatically driven piston pumps from WAGNER are explosion-proof and therefore are suitable for use in workshops.

2. NO CONTINUOUS RUNNING:

Piston pumps only operate when you have to build up pressure. The rest of the time, the drive is on 'standby'. This protects wear parts and has a positive impact on site noise levels.

CROSS-SECTION OF THE PISTON




upper packing

lower packing
inlet-valve

outlet-valve

ADVANTAGES

- Powerful suction
- Better delivery capacity with high viscosity materials
- Less sensitive to filled materials
- Large nozzle sizes can be used
- Extra-durable packing



PROSPRAY 3.20 HEA SPRAYPACK

The compatible piston pump for Airless beginners



- **Robust and simple:** perfect for use on the construction locations, reliable, easily accessible high quality packings
- **Good performance at an attractive price:** for medium-sized projects, ideal for interior emulsion paints
- **Innovative, low-pressure airless technology:** up to 55 % less overspray due to HEA technology



- **With flexible suction system:** for simple intake directly from the original container
- **Well-proven piston pump:** ideal for comfortable transport and space-saving storage



Included: tool bag with two open-end spanners

User-friendly: easy to operate and a reduced number of settings options makes starting up the sprayer easier.

HEA 517 nozzle: for a soft spray pattern and up to 55 % less spray mist

HEA pressure gauge: a longer service life thanks to innovative HEA low-pressure airless technology

Inlet pusher valve: for a high operating reliability and easy commissioning. Just the press of a finger, and the valve is free

Hose rewind: for optimised storage of the hose

Double-Acting-piston pump: for consistent material feed



≤ 0.021"; 1.6 l/min

PROSPRAY 3.20 HEA SPRAYPACK

ProSpray 3.20 basic unit	-
HP hose DN6, 27 MPa, NPSM 1/4", 15 m	9984574
Flexible suction system	0558672
Pressure gauge set assy. HEA(MPa)	2383995
Airless Vector Pro gun; 1/4"; incl. TradeTip 3 nozzle holder; with 4-finger trigger	538040
HEA ProTip 517	554517

PROSPRAY 3.20 HEA SPRAYPACK - DPPS 2412438

ACCESSORIES

Nozzle extension, 15 cm, G-thread	556074
Nozzle extension, 30 cm, G-thread	556075
5 litre hopper	704-453
HEA ProTip various sizes (e.g. 211 – Art-No 554211)	554XXX
TradeTip3 Fine Finish various sizes	554XXX
TipClean 200 ml	2400214
HP hose DN4, 27 MPa, NPS 1/4", 7.5 m	9984573
Lack Kit (DN 4) for ProSpray pumps	2406206

PROSPRAY 20 HEA SPRAYPACK



The robust piston pump for Airless beginners

- **Built tough:** for a long service life on the construction site
- **Compact and simple design**
- **Easy handling:** thanks to HEA technology
- **Optimised lifetime and performance**



- **Innovative ProSpray product features:** for example new packings

PROSPRAY 3.21 HEA SPRAYPACK



Small and compact – for small object sizes

- **Innovative, low-pressure airless technology:** up to 55 % less overspray
- **Optimum value-for-money:** Ideal for all users who mostly spray-coat small surfaces on a daily basis
- **For trouble-free operation:** Integrated high-pressure filter



- **Compact design with outstanding performance data:** 0.023" nozzle size, 2.0 l/min max., delivery rate: 16 kg weight
- **With flexible suction system:** for simple intake directly from the original container

Compact: for easy transportation and space-saving storage


HEA Pressure Gauge: longer life thanks to innovative HEA low-pressure airless technology

Practical cable wrap: for tidy storage of the electric cable

HEA 517 nozzle: soft spray pattern and up to 55% less overspray

DN6, 15 m high-pressure hose: for a large radius of action

Drip cup: possible residues in the suction hose can be captured during transport



HEA HIGH EFFICIENCY AIRLESS

Compact: for easy transportation and space-saving storage


Maintenance made easy: With the push of a button the piston is oiled and thus the packings are conserved.

HEA Pressure Gauge: longer life thanks to innovative HEA low-pressure airless technology

HEA 517 Tip: soft spray pattern and up to 55% less overspray

DN6, 15 m high-pressure hose: for a large radius of action

Inlet pusher valve: for a high operating reliability and easy commissioning. Just the press of a finger, and the valve is free.



HEA HIGH EFFICIENCY AIRLESS

T ≤ 0.021"; **W** 1.6 l/min

PROSPRAY 20 HEA SPRAYPACK - DPPS 2403616

ProSpray 20, basic unit	-
HP hose DN6, 27 MPa, NPSM 1/4", 15 m	9984574
Flexible suction system	0558672A
Pressure gauge set assy. HEA(MPa)	2383995
Airless Vector Pro gun, 1/4", incl. TradeTip 3 nozzle holder, with 4-finger trigger	538040
HEA ProTip 517	554517

ACCESSORIES

HEA ProTip, different sizes (e.g. tip 211 - Art.No. 517211)	554XXX
TradeTip 3 FineFinish nozzles, different sizes	554XXX
5 litre hopper	704-453
HP hose DN4, 27 MPa, NPS 1/4", 7.5 m	9984573
Nozzle extension, 15 cm, G-thread	556074

T ≤ 0.023"; **W** 2 l/min

PROSPRAY 3.21 HEA SPRAYPACK - DPPS 532089

Basic unit, PS 3.21	-
HP hose DN6, 27 MPa, NPSM 1/4", 15 m	9984574
Pressure gauge set assy. HEA(MPa)	2383995
Airless Vector Grip gun, 1/4", incl. TradeTip 3 nozzle holder, with 2- and 4-finger trigger	538043
HEA ProTip 517	554517

ACCESSORIES

TradeTip 3 FineFinish nozzles, different sizes (e.g. tip 211 - Art. No. 517211)	554XXX
Nozzles TradeTip 3, different sizes	553XXX
Nozzle extension, 15 cm, G-thread	556074
Nozzle extension, 60 cm, G-thread	556077
TipClean; 200ml	2400215
EasyGlide, special oil, 118 ml	508619

PROSPRAY 3.25 SPRAYPACK



A compact emulsion unit for medium-sized objects

- **Innovative ProSpray product features:** Digital information readout and unit control directly on the device - piston oiled at the touch of a button - inlet valve depressor for high operating reliability - and more
- **Easy to handle:** Compact design for ease of transport and space-saving storage



- **Lightweight:** Just 17.9 kg (skid version) or 27.4 kg (cart version)
- **Two versions:** Available on trolley or as a compact Skid version

Clearly arranged - DESC-Control:

With the digital display you can read out and handle machine data, consumption figures, runtimes and much more. The intelligent deadband control, SlowMotion function and FrequentClean guarantee trouble-free work and quick cleaning

Maintenance-free, brushless direct current motor:

Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure

Superb Spray Surface Quality: with the Vector Grip Airless gun. Light in weight with a long service life

Maintenance made easy: With the push of a button the piston is oiled and thus the packings are conserved

Inlet pusher valve: for a high operating reliability and easy commissioning. Just the press of a finger, and the valve is free

Also available as skid version



≤ 0.027"; 2.6 l/min

PROSPRAY 3.25 SPRAYPACK - DPPS

Basic unit, PS 3.25 on cart	-
HP hose DN6, 27 MPa, NPSM 1/4", 15 m	9984574
Airless Vector Grip gun, 1/4", incl. TradeTip 3 nozzle holder, with 2- and 4-finger trigger	538043
2SpeedTip, D10, 111 / 419	271045

PROSPRAY 3.25 SPRAYPACK - SKID VERSION 2308259

PROSPRAY 3.25 SPRAYPACK - CART VERSION 2308260

ACCESSORIES

TradeTip 3 FineFinish nozzles, different sizes (e.g. tip 211 - Art. No. 517211)	554XXX
Nozzles TradeTip 3, different sizes	553XXX
Nozzle extension, 15 cm, G-thread	556074
Nozzle extension, 60 cm, G-thread	556077
TipClean; 200ml	2400215
EasyGlide, special oil, 118 ml	508619



PROSPRAY 3.31 SPRAYPACK



A reliable unit for large-area emulsion work

- **Electronic control, information and management directly on the device:** displays the current pressure, pressure settings can be set and displayed, and much more
- **No-maintenance brushless motor**



- **High coverage performance together with easy operation**
- **Innovative ProSpray product features:** Digital information readout and unit control directly on the device - tilting carriage - integrated high-pressure filter - and more

Superb Spray Surface Quality: with the Vector Grip Airless gun. Light in weight with a long service life

No nozzle blockages: The high pressure filter is easily accessible and quick to clean. Three different filter inserts (fine, medium, coarse) ensure an optimal match with the material

Tilting cart: Fast change of the container. Site-optimised tyres allow convenient pump transport

Maintenance-free, brushless direct current motor: Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure

Clearly arranged - DESC-Control:

With the digital display you can read out and handle machine data, consumption figures, runtimes and much more. The intelligent deadband control, SlowMotion function and FrequentClean guarantee trouble-free work

≤ 0.032"; 3.8 l/min

PROSPRAY 3.31 SPRAYPACK - DPPS

Basic unit, ProSpray 3.31	-
HP hose DN6, 27 MPa, NPSM 1/4", 15 m	9984574
Airless Vector Grip gun, 1/4", incl. TradeTip 3 nozzle holder, with 2- and 4-finger trigger	538043
2SpeedTip, D20, 115/421	271046

ACCESSORIES

TradeTip 3 FineFinish nozzles, different sizes (e.g. tip 211 - Art. No. 517211)	554XXX
Nozzles TradeTip 3, different sizes	553XXX
Nozzle extension, 15 cm, G-thread	556074
Nozzle extension, 60 cm, G-thread	556077
TipClean; 200ml	2400215
EasyGlide, special oil, 118 ml	508619



PROSPRAY 3.34 SPRAYPACK



A technology masterpiece for high-viscosity materials such as flame retardants and corrosion-proofing products

- **This high-performance piston pump:** is ideally suited for large building sites where it is also able to handle high-viscosity materials
- **No-maintenance brushless motor**
- **For large building sites:** Powerful and robust



- **Faster than ever:** Quick-change fluid section for ease of servicing and shorter reaction times
- **Innovative ProSpray product features:** Digital information readout and unit control directly on the device - tilting cart - integrated high-pressure filter - and more.

Superb Spray Surface Quality: with the Vector Grip Airless gun. Light in weight with a long service life

No nozzle blockages: The high pressure filter is easily accessible and quick to clean. Three different filter inserts (fine, medium, coarse) ensure an optimal match with the material

Tilting cart: Fast change of the container. Site-optimised tyres allow convenient pump transport

Clearly arranged - DESC-Control: With the digital display you can read out and handle machine data, consumption figures, runtimes and much more. The intelligent deadband control, SlowMotion function and FrequentClean guarantee trouble-free work and quick cleaning

Maintenance-free, brushless direct current motor: Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure

Low maintenance costs: The practical, self-adjusting packings lead to less wear and are easy to change. They have a service life up to 50% longer than comparable packings

Simple and quick: Change of the suction system without tools

≤ 0.034"; 4.5 l/min

PROSPRAY 3.34 SPRAYPACK - DPPS 2308263

Basic unit, PS 3.34	-
HP hose DN6, 27 MPa, NPSM 1/4", 15 m	9984574
Airless Vector Grip gun, 1/4", incl. TradeTip 3 nozzle holder, with 2- and 4-finger trigger	538043
2SpeedTip, D20, 115/421	271046

ACCESSORIES

TradeTip 3 FineFinish nozzles, different sizes (e.g. tip 211 - Art. No. 517211)	554XXX
Nozzles TradeTip 3, different sizes	553XXX
Nozzle extension, 15 cm, G-thread	556074
Nozzle extension, 60 cm, G-thread	556077
TipClean; 200ml	2400215
EasyGlide, special oil, 118 ml	508619



PROSPRAY 3.39 SPRAYPACK



Powerful emulsion unit for large areas

- **More power:** Greater suction performance thanks to the low position of the suction valve
- **Twice as fast with emulsion:** Parallel two-gun operation possible
- **The most powerful pump in the ProSpray family:** Even able to cope with Airless spraying fillers



- **Innovative ProSpray product features:** Tilting cart - change paints without using tools

Superb Spray Surface Quality: with the Vector Grip Airless gun. Light in weight with a long service life

No nozzle blockages: The high pressure filter is easily accessible and quick to clean. Three different filter inserts (fine, medium, coarse) ensure an optimal match with the material

Tilting cart: Fast change of the container. Site-optimised tyres allow convenient pump transport

Clearly arranged - DESC-Control: With the digital display you can read out and handle machine data, consumption figures, runtimes and much more. The intelligent deadband control, SlowMotion function and FrequentClean guarantee trouble-free work and quick cleaning

Maintenance-free, brushless direct current motor: Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure

Low maintenance costs: The practical, self-adjusting packings lead to less wear and are easy to change. They have a service life up to 50% longer than comparable packings

Also available as filler version with Airless gun AG 19

≤ 0.039"; 5 l/min

PROSPRAY 3.39 EMULSION SPRAYPACK - DPPS 2351261

Basic unit, PS 3.39	-
HP hose DN6, 27 MPa, NPSM 1/4", 15 m	9984574
Airless Vector Grip gun, 1/4", incl. TradeTip 3 nozzle holder, with 2- and 4-finger trigger	538043
2SpeedTip, D40, 117/427	271048
Double connector A = 1/4" NPS x 3/8" NPT	812-003
Double connector A = 3/8" NPT x A = 1/2" NPS	815-005

PROSPRAY 3.39 FILLER SPRAYPACK - DPPS 2308264

Basic unit, PS 3.39	-
HP hose DN13, max. 25 MPa, 3/8", NPSM 1/2", 15 m	2336585
Hose whip DN10, max. 25 MPa, NPSM 3/8", 2.5 m	2336582
Airless gun AG 19, 25 MPa, G-thread 3/8", incl. TradeTip 3 nozzle holder	2341127
2SpeedTip, S10, 235/527	271049
Coupling sleeve I = 1/4"NPSM x A = 3/8"NPSM, 27 MPa	179732
Connector 3/8" x 1/2"	814-005



	PROSPRAY 3.20 HEA	PROSPRAY 20 HEA	PROSPRAY 3.21 HEA	PROSPRAY 3.25 - SKID VERSION	PROSPRAY 3.25 - CART VERSION
Product image (may differ)					
Spraying method					
Technology					
Drive					
Voltage	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Motor output	1.0 kW	0.9 kW	1.03 kW	1.1 kW	1.1 kW
Max. operating pressure	207 bar, 20.7 MPa	214 bar, 21.4 MPa	221 bar, 22.1 MPa	221 bar, 22.1 MPa	221 bar, 22.1 MPa
Max. delivery rate	1.6 l/min	1.6 l/min	2 l/min	2.6 l/min	2.6 l/min
Max. nozzle size	0.021"	0.021"	0.023"	0.027"	0.027"
Recommended max. hose length	30 m	30 m	30 m	30 m	30 m
Max. viscosity	20.000 mPas	20.000 mPas	20.000 mPas	25.000 mPas	25.000 mPas
Weight	13.6 kg	15.2 kg	17.9 kg	17.9 kg	27.4 kg
Art. No.	2412438	2403616	532089	2308259	2308260
Categorie	DPPS	DPPS	DPPS	DPPS	DPPS
Material					
Recommended intensity					

	PROSPRAY 3.31	PROSPRAY 3.34	PROSPRAY 3.39 EMULSION	PROSPRAY 3.39 FILLER
Product image (may differ)				
Spraying method				
Technology				
Drive				
Voltage	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Motor output	1.84 kW	1.95 kW	2.19 kW	2.19 kW
Max. operating pressure	221 bar, 22.1 MPa	221 bar, 22.1 MPa	221 bar, 22.1 MPa	221 bar, 22.1 MPa
Max. delivery rate	3.8 l/min	4.5 l/min	5 l/min	5 l/min
Max. nozzle size	0.032"	0.034"	0.039"	0.039"
Recommended max. hose length	60 m	60 m	60 m	60 m
Max. viscosity	25.000 mPas	25.000 mPas	30.000 mPas	30.000 mPas
Weight	43.5 kg	47.6 kg	50 kg	50 kg
Art. No.	2308262	2308263	2351261	2308264
Categorie	DPPS	DPPS	DPPS	DPFSF
Material				
Recommended intensity				

Water and solvent-based lacquers, lacquer paints, oils, separating agents

Synthetic resin varnishes, PVC lacquers, 2K lacquers

Primers, fillers

Fire protection, rust protection paints

Emulsion and latex paints, adhesives, sealants

Exterior paints, roof coatings, floor coatings, textured paint

Structural waterproofing, bituminous coatings

Filler

Plaster

Residential

Large residential

Commercial

XVLP / HVLP

AirCoat

Piston pump

Double diaphragm pump

Electric

Explosion-protection

FineSpray

Airless

Diaphragm pump

Turbine

Pneumatic

TempSpray

Plaster spraying

Spiral pumps

Petrol-driven

NOZZLES

The heart of the spraying process

Across all technologies – Airless, AirCoat, plaster spraying with worm pumps, HVLP or XVL P – nozzles and air caps play a decisive role in surface quality. In addition to the actual pump, they are the true heart of the spraying process. This is where the material is atomised and where the fineness of the droplet formation in the spray pattern is determined. The nozzle size also determines the quantity of material forced through the bore. Top-quality nozzles are a prerequisite for premium surface finishes in line with your professional standards.



	Water and solvent-based lacquers, lacquer paints, oils, separating agents		Synthetic resin lacquers, PVC lacquers, 2K lacquers		Primers, fillers
	Fire protection, rust protection paints		Emulsion and latex paints, adhesives, sealants		Exterior paints, roof coatings, floor coatings
	Structural waterproofing, bituminous coatings		Filler		Plaster



AIRLESS TRADETIP 3 NOZZLES – PERFECT AND DURABLE

Art. no. 553xxx The yellow standard nozzle covers a wide spectrum of applications using primers, enamels and lacquers.

Jet width (mm)*	Orifice size (inch)																									
	0,007	0,009	0,011	0,013	0,015	0,017	0,019	0,021	0,023	0,025	0,027	0,029	0,031	0,033	0,035	0,039	0,043	0,045	0,051	0,052	0,055	0,061	0,063	0,065	0,067	
100	107	109	111	113	115	117																				
120	207	209	211	213	215	217	219	221	223	225	227	229	231	233	235		243			252		261	263		267	
150	307	309	311	313	315	317	319	321	323	325	327	329	331	333	335											
190	407	409	411	413	415	417	419	421	423	425	427	429	431	433	435	439	443	445	451		455	461	463		467	
225		509	511	513	515	517	519	521	523	525	527	529	531	533	535	539	543	545	551		555	561		565		
270		609	611	613	615	617	619	621	623	625	627	629	631	633	635	639	643		651		655	661		665		
300					715	717	719	721	723	725			731		735											
330				813	815	817	819	821	823	825	827		831													
385							919																			
Flow rate (l/min)**	0,19	0,34	0,45	0,68	0,91	1,17	1,47	1,78	2,15	2,53	2,95	3,44	3,89	4,42	4,99	6,20	7,52	8,24	10,58							
Filter	red			yellow			white						green													



HEA PRO TIP NOZZLES – UP TO 55 % LESS OVERSPRAY

Art. no. 554xxx The new WAGNER HEA ProTip airless nozzle provides a perfect surface finish at reduced spraying pressure. Compared to standard airless technology the spray pattern is gently feathered and free from edge strips.

Jet width (mm)*	Orifice size (inch)						Spray angle in °
	0,011	0,013	0,015	0,017	0,019	0,021	
120	211	213					20
150	311	313					30
190	411	413	415	417		421	40
225			515	517	519	521	50
270			615	617	619	621	60
Flow rate (l/min)**	0,45	0,68	0,91	1,17	1,47	1,78	
Filter	red		yellow		white		



AIRLESS TRADETIP 3 FINEFINISH

Art. no. 554xxx Top paint nozzle with optimised third-generation properties. With double special core for ultra-fine droplet formation and exceptionally high-quality surfaces, even in low pressure ranges. FineFinish nozzles are coloured purple.

Jet width (mm)*	Orifice size (inch)				Spray angle in °
	0,008	0,010	0,012	0,014	
120	208	210	212	214	20
150	308	310	312	314	30
190	408	410	412	414	40
225		510	512	514	50
Flow rate (l/min)**	0,26	0,42	0,6	0,79	
Filter	red				


* Spray width (mm) at approx. 30 cm distance from the object and 100 bar pressure, with synthetic resin paint, 20 DIN seconds
 ** Measured with water at 120 bar pressure

ACCESSORIES – PROSPRAY


SPEEDSHIELD

SpeedShield 0538905

No ladders or scaffolding - The Pole-gun extends your workingradius



SpeedShield - trimming without masking; delivered without Tip and extension




POLE GUNS

Pole gun 120 cm, 1/4" nozzle holder, G-thread 7/8"	0296441
Pole gun 200 cm, 1/4" nozzle holder, G-thread 7/8"	0296442


PAINT ROLLERS

Inline Roller IR 100 incl. HP hose DN4, max. 27 MPa, 7.5m, extension 0.5m, woven plush paint roller, short pile 13 mm and much more	0345010
Innerfeed Roller incl extension (0.9 m)	2420499
SprayRoller Cage incl. extension (0.9 m)	2420496
SprayRoller Frame incl. extension (0.9 m)	2420497
Gun extension incl. extension (0.9 m)	2420538



Airless paint roller - rational coating with paint roller

Nozzle extension - for more comfortable working and a wider reach



NOZZLE EXTENSIONS

Nozzle extension, 15 cm, G-thread	0556074
Nozzle extension, 30 cm, G-thread	0556075
Nozzle extension, 45 cm, G-thread	0556076
Nozzle extension, 60 cm, G-thread	0556077

CLEANING AND STORAGE

TipClean, container incl. special cleaner; 200 ml	2400214
EasyClean Cleaning and corrosion protection 1 L	2412656
EasyGlide, special oil, 118 ml	508619



TipClean - easy cleaning and storage of your airless nozzles

SPRAYGUIDES



More SprayGuides:
go.wagner-group.com/sprayguide

MACHINE & MATERIAL PERFECTLY MATCHED

The extensive WAGNER SprayGuide offers you test reports from well-known material manufacturers for use with WAGNER spray machines.

Visit sprayguide.wagner-group.com to find out how to set up your machine to match the material you are using, and which paints and lacquers can be sprayed most effectively with WAGNER technology.

- ➔ Search by material type
- ➔ Search by material manufacturer
- ➔ Search by WAGNER machine and systems

INNOVATION SINCE 1947

Perfect surfaces and added value are our passion. Bringing colour, protection and function to surfaces is our mission. We dedicate all of our technical expertise to your objects and products, and support you with personal service. Using innovative technologies and highly efficient, reliable and user-friendly solutions, we are constantly setting new standards in surface technology.



Anyone purchasing a WAGNER paint spraying unit automatically receives a three-year manufacturer's warranty. But we can do more: If you register online, you can extend this warranty for a further two years, free of charge!

go.wagner-group.com/3plus2

BE UNSTOPPABLE!

VISIT US AT

