INOTEC GmbH







Delivery pump: inoBEAM M8



inoBEAM M8

The handy 230 V peristaltic delivery pump for liquid and paste-like materials

Benefits at a glance

- Light, small and handy
- For liquid and paste-like materials
- Extremely gentle peristaltic pump technology
- Simple operation
- Very quick cleaning and maintenance
- Variable volume control
- Dry-run safe
- Removable plastic material hopper
- Forward and reverse running
- Can be combined with large containers (drum)



The **inoBEAM M8** delivery pump handles materials based on the "walk principle". A flexible rubber disc pushes the material to be conveyed through the pump housing and into the material hose. This delivers a considerable benefit: less frictional heat is generated and the material is conveyed very efficiently.

The very fast cleaning and simple maintenance processes keep operating costs low and save time.

Areas of application

Waterproofing materials (1k, 2k, cementitous or bituminous), acoustic fillers and plasters, top coats, fillers and paints, and many more

Technical data

Operating pressure max. 15 bar

Operating voltage 230 V / 16 A / 50 Hz

Motor rating 0.55 kW 0 - 8 l/min Delivery rate Delivery range up to 30 m* Delivery height up to 20 m*

Material hopper 30 I

Dimensions

600 x 230 x 750 mm

 $(L \times W \times H)$

Weight approx. 28 kg

* Depending on the material consistency



Brilliant

inoBEAM M8 **Waterproofing Set**

Item no. 10042326

Scope of delivery

As with the basic module (item no. 10000080-008)

- Combined material hose, Ø 1", 10 m
- · Angled spray head with GEKA coupling inc. 8 mm nozzle
- Remote control cable, 16 m
- · Cover for material hopper



INOTEC GmbH • Daimlerstraße 9-11 • D-79761 Waldshut-Tiengen • T.: +49 77 41 / 68 05-0 • www.inotec-gmbh.com

Brilliant Spraytec Sdn. Bhd. • No. 1-11A 1, Jalan Desa 1/5, Taman Desa Aman Puri • 52100 Kepong, Kuala Lumpur, Malaysia • T. +603-6277 8799 • www.brilliantspraytec.com